




Navigation and Ancillary Information Facility

SPICE Conventions

A summary of many “standards,” lingo
and common usage within SPICE

October 2007



SPICE Lexicon - 1

Navigation and Ancillary Information Facility

SPICE

- The name of this ancillary information system

NAIF

- The name of the team of people at JPL who lead development of the SPICE system.
- Also the name of the ancillary data node of NASA's Planetary Data System (PDS).

Satellite


- Refers only to a natural satellite of a planet—not a spacecraft



SPICE Lexicon - 2

Navigation and Ancillary Information Facility

SPICE Toolkit	<ul style="list-style-type: none">Names that refer to the principal collection of software produced by JPL's NAIF Team as part of the SPICE information system. May include mission- or domain-specific augmentations.
NAIF Toolkit	
The Toolkit	
Generic Toolkit	<ul style="list-style-type: none">A Toolkit that contains no mission-specific or enterprise-specific augmentations. This is what is available from NAIF's website.
SPICELIB	<ul style="list-style-type: none">The principal user library found within Fortran versions of the Toolkit.
CSPICE	<ul style="list-style-type: none">The principal user library found within C versions of the Toolkit. Also used to refer to the entire C Toolkit.
Icy	<ul style="list-style-type: none">An IDL interface to CSPICE
Mice	<ul style="list-style-type: none">A MATLAB interface to CSPICE



SPICE Lexicon - 3

Navigation and Ancillary Information Facility


- **Text kernel**
 - Any kernel type consisting entirely of ASCII information, with each line terminated using the local operating system convention (CR, LF, CR+LF)
 - Text kernel types are FK, IK, text PCK, LSK, SCLK, MK ("Furnsh")
 - Any and all text kernels could be combined in a single file.
 - » But this is certainly not recommended!
- **Binary kernel**
 - Any kernel type using binary file format
 - Binary types are SPK, binary PCK, CK, ESQ and DSK
 - Different binary kernel types can not be combined together in a single file
- **Transfer format kernel**
 - A hexadecimal (ASCII) version of a binary kernel, used ONLY for porting a binary kernel between incompatible computers.
 - Not as important as it was prior to the addition of the so-called "binary kernel run-time translation" capability in N0052.
 - » But still has a role in making native binary kernels required for some operations.



SPICE Lexicon - 4

Navigation and Ancillary Information Facility

- **Database Kernel (DBK)**
 - A SPICE kernel that, in conjunction with Toolkit DBK software, provides a self-contained SQL-like database capability.
- **“Command file”**
 - Many SPICE application and utility programs either require, or optionally accept, an input file containing program directives and sometimes input data. Unfortunately NAIF has not used a consistent approach for referring to such files. The following names have been used:
 - » Setup file, preferences file, command file, specifications file, definitions file



SPICE Lexicon - 5

Navigation and Ancillary Information Facility

- **Deprecated software**
 - Code that, while still useable, has been superseded with a newer and presumably better version
 - We encourage you to not use deprecated SPICE software
 - » (But, for your convenience, we won't remove it from the Toolkit packages) 😊
- **Toolkit version naming**
 - "Nxxxx" e.g. N0061 is version 61
 - » Often shortened to just Nxx (e.g. N61)



SPICE Lexicon - 6

Navigation and Ancillary Information Facility

Names used synonymously


- Kernel, SPICE file, SPICE kernel, SPICE kernel file
- Metadata, comments
- Time, Epoch
- Encoded SCLK, ticks*
- Frame, Reference Frame**
- Ephemeris, trajectory
- Rectangular coordinates, Cartesian coordinates**
- Geodetic, Planetodetic (coordinate system)
- Ephemeris time (ET), Barycentric Dynamical Time (TDB)
- Attitude and orientation
- International Celestial Reference Frame (ICRF) and Earth Mean Equator and Equinox of 2000 (J2000) reference frame
- Meta-kernel and Furnsh kernel
- Module, routine, subroutine, procedure, and function (in C and MATLAB)
- “Body”, “solar system object” and “ephemeris object”

* Encoded SCLK always refers to absolute time; “ticks” is used to refer to both durations and absolute times.

** Outside of SPICE the term “coordinate system” is often used synonymously with “frame” or “reference frame.” We prefer to use “coordinate system” in the sense of describing how coordinates are measured (e.g. cylindrical coordinate system, Cartesian coordinate system, polar coordinate system, etc), and to use “frame” in the sense of a set of three orthogonal

SPICE Conventions vectors.

7



Kernel File Names

Navigation and Ancillary Information Facility

- **SPICE imposes only one restriction on kernel file names**
 - No white space allowed within a name
- **NAIF suggests names conform to the PDS standard: “27.3”**
 - <1 to 27 alphanumeric characters>. <1 to 3 chars>
- **Common usage within NAIF for SPICE kernel file name extensions is listed on the next page, with the following general style used:**
 - t* text format (e.g. leapseconds.tls)
 - b* binary format (e.g. de405.bsp)
 - x* transfer format (e.g. de405.xsp)



Common SPICE Kernel File Name Extensions

Navigation and Ancillary Information Facility

SPK:

.bsp binary format SPK file
.xsp transfer format SPK file

PcK:

.tpc text format PcK file
(This is the most common type PcK)
.bpc binary PcK file
(few instances of this)
.xpc transfer format PcK file
(few instances of this)

IK:

.ti text format IK file

FK:

.tf text format FK file

LSK:

.tls text format LSK file

CK:

.bc binary format CK file
.xc transfer format CK file

SCLK:

.tsc text format SCLK file

MK:

.tm text format Meta-kernel file ("FURNISH kernel")

DSK:

.bds binary format DSK file

EK Family (ESP, ESQ, ENB)

ESP:

.tep text format Science Plan EK file

ESQ:

.bes binary format Sequence Component EK file
.xes transfer format Sequence Component EK file


ENB:

n/a (www interface)

These are suggestions, not requirements

SPICE Conventions

9



Common Document Name Extensions

Navigation and Ancillary Information Facility

- These extensions are used for plain ASCII documents included with each Toolkit delivery
 - .ug** User's Guide
 - .req** "Required Reading" reference document
 - .txt** Used for a few miscellaneous documents
 - .idx** Used only for the permuted index document
- All HTML documents included in the Toolkit have extension **.html**
- Alternate formats of some of the Toolkit documents are available from the NAIF anonymous ftp server
 - .pdf** PDF documents

SPICE Conventions

10



Public and Private Modules

Navigation and Ancillary Information Facility

- All Toolkits include public and private modules
- Public modules are available for your use
 - Names of public APIs are different in the four SPICE library implementations. For example, the top level SPK reader SPKEZR has the following names
 - » in SPICELIB (FORTRAN) SPKEZR
 - » In CSPICE (C) spkezt_c
 - » ICY (IDL) cspice_spkezt
 - » Mice (MATLAB) cspice_spkezt and spkezt_mice
 - The API Reference Guide included in the Toolkit HTML documentation provides the complete list of all public SPICE APIs available in a specific implementation of the Toolkit
- Private modules are for NAIF staff use only
 - Names of private modules start with “ZZ”
 - They are present in the Toolkit only to support operations of “public” modules
 - Private APIs are not listed in the API Reference Guide but can be seen in the source code directories for SPICELIB, CSPICE, and Mice
 - Do not use “private” modules in your code – they may change



Reference Frame and Coordinate System Conventions

Navigation and Ancillary Information Facility


- All reference frames used within SPICE are right handed systems
 - $X \text{ cross } Y = Z$
- In planetocentric coordinate systems the +Z axis (+90 LAT) always points to the north side of the invariable plane (the plane whose normal vector is the angular momentum vector of the solar system)
 - Planetocentric longitude increases positively eastward
 - Planetocentric latitude increases positively northward
- In planetographic coordinate systems:
 - Planetographic longitude is defined such that the sub-observer longitude increases with time as seen by a distant, fixed observer in an inertial reference frame
 - » The earth, moon and sun are exceptions; planetographic longitude is positive east by default
 - Planetographic latitude increases positively northward



Quaternions

Navigation and Ancillary Information Facility

- There are different “styles” of quaternions used in science and engineering applications. Styles are characterized by
 - The order of the quaternion elements
 - The quaternion multiplication formula
 - The convention for associating quaternions with rotation matrices
- Two of the commonly used styles are
 - “SPICE”
 - » Used by Sir William Rowan Hamilton (discoverer of quaternions)
 - » Used in math and physics textbooks
 - “Engineering” or “MSOP”
 - » Widely used in JPL ACS/AACS and other aerospace applications
- Relationship between SPICE and MSOP quaternions:
 - Let M be a rotation matrix such that for any vector v , $M*v$ is the result of rotating v by Θ radians in the counterclockwise direction about unit vector A . Then the quaternions representing M are:
 - » SPICE: $(+/-) (\cos(\Theta/2), \sin(\Theta/2)A(1), \sin(\Theta/2)A(2), \sin(\Theta/2)A(3))$
 - » MSOP: $(+/-) (-\sin(\Theta/2)A(1), -\sin(\Theta/2)A(2), -\sin(\Theta/2)A(3), \cos(\Theta/2))$
- Details about SPICE quaternions are found in:
 - Rotations Required Reading document
 - NAIF white paper on quaternions: ftp://naif.jpl.nasa.gov/pub/naif/misc/Quaternion_White_Paper/
 - SPICE quaternion conversion routines: M2Q, Q2M



Names and IDs

Navigation and Ancillary Information Facility

- Many items within SPICE have assigned names (text strings) and IDs (integer numbers)
- The NAIF/SPICE rules, standards, practices and exceptions regarding these names and IDs are discussed in a separate tutorial (“Names and IDs”)