



Navigation and Ancillary Information Facility

Introduction to Kernels

June 2019
(Class version)




What is a SPICE “Kernel”

Navigation and Ancillary Information Facility

“Kernel” means file

“Kernel” means a file containing ancillary data


“Kernel” means a file containing "low level" ancillary data that may be used, along with other data and SPICE Toolkit software, to determine higher level observation geometry parameters of use to scientists and engineers in planning and carrying out space missions, and analyzing data returned from missions.




SPICE Kernels Family

Navigation and Ancillary Information Facility

- **SPK**
 - Spacecraft and Planet Ephemeris
- **PCK**
 - Planetary Constants, for natural bodies
 - » Orientation
 - » Size and shape
- **IK**
 - Instrument
- **CK**
 - Orientation (“Camera-matrix”)
- **EK**
 - Events, up to three distinct components
 - » ESP: science plan
 - » ESQ: sequence
 - » ENB: experimenter’s notebook
- **FK**
 - Reference frame specifications
- **SCLK**
 - Spacecraft clock correlation data
- **LSK**
 - Leapseconds
- **MK**
 - Meta-Kernel (a.k.a. “FURNISH kernel”)
 - Mechanism for aggregating and easily loading a collection of kernel files
- **DSK**
 - Digital shape kernel
 - » Tessellated plate model
 - » Digital elevation model (under development)
- **DBK**
 - Database mechanism
 - » Primarily used to support the ESQ




EK is rarely used



SPICE Kernel Forms

Navigation and Ancillary Information Facility

- **Binary form**
 - A file mostly containing data encoded in binary form
 - Provides rapid access to large amounts of numeric data
 - Binary kernels are not human-readable; they require the use of Toolkit software to examine the data contents
- **Text form**
 - Plain text files containing only printing characters (ASCII values 32-126), i.e. human-readable text.



Text and Binary Kernels

Navigation and Ancillary Information Facility

SPICE **text** kernels are:

- text PCK (the most common type of PCK)
- IK
- FK
- LSK
- SCLK
- MK

SPICE **binary** kernels are:


- SPK
 - binary PCK (has been used only for Earth, Moon and Eros)
 - CK
 - DSK

 - ESQ (part of the E-kernel)
 - DBK (database kernel)
- } Rarely used



Kernel Architecture

- Text kernels
- Binary kernels
- Comments in kernels




Text Kernel Contents

Navigation and Ancillary Information Facility

- **A text kernel is a plain text file of ASCII data**
- **It contains assignments of the form:**


```
variable_name = value(s)
```

- **A text kernel should also contain descriptive comments that describe the assignments**
 - **Comments are sometimes referred to as “meta-data”**
 - » **Don’t confuse this usage with the “meta-kernel” described later in this tutorial**




Example Text Kernel

Navigation and Ancillary Information Facility



- The next several pages describe what you see above
- See the “Kernel Required Reading” document for details



Text Kernel Formatting

Navigation and Ancillary Information Facility


- `KPL/<text kernel type>`
 - Its use is optional, but is highly recommended
 - Must appear on the first line, starting in column 1
 - Tells SPICE software what kind of kernel it is
 - Text kernel types are FK, IK, PCK, SCLK, MK
- `\begindata` and `\begintext`
 - Markers, on lines by themselves, which set off the beginning of data and the beginning of comment (metadata) blocks respectively
 - They need not begin in column 1
- `<LF>` for Unix/Linux/Mac or `<CR><LF>` for Windows
 - End of line marker (usually not visible when displaying a text kernel)
 - Must be present on EVERY line in the text kernel
- **Max line length, including any white space, is 132 characters**



Text Kernel Operators

Navigation and Ancillary Information Facility


- An assignment using the “=” operator associates one or more values with a variable name.
- An assignment using the “+=” operator associates additional values with an existing variable name.
- An assignment using the “@” symbol associates a calendar date with a variable name.
 - The string will be parsed and converted to an internal double precision representation of that epoch as seconds past the J2000 epoch
 - » There is no time system implied
 - » This conversion does not need a leap seconds kernel



Variable Names and Values

Navigation and Ancillary Information Facility

- **Variable names**
 - Max of 32 characters
 - Are case sensitive (recommendation: use only upper case)
 - Cannot include space, period, parenthesis, equals sign or tab
 - Recommendation: don't use the “+” sign as the last character
- **Values**
 - Numeric: integer, fixed point and scientific notation are allowed
 - String:
 - » enclosed in single quotes
 - » maximum length of 80 characters on a given line
 - SPICE has means to concatenate multiple string values to allow for values exceeding 80 characters
 - » string values may contain any printing ASCII character, including blank
 - Time: identified by the “@” character
 - Any of these three types can be provided as an n-dimensional vector of values
 - » Components are separated by commas or white space (but not TABs)
 - » Parentheses are used to enclose the vector
 - » Each string value in a vector is contained in single quotes
 - » Values in a vector must all be of the same type (numeric, string or time)
- See “Kernel Required Reading” for more information




Variable Names and Values

Navigation and Ancillary Information Facility


- A “picture” of the most basic text kernel assignment rules

132 max characters, with the non-printing system-dependent end-of-line indicator at the end*



*Unix, Linux, OSX EOL symbol: <LF>

*DOS/Windows EOL symbol: <CR><LF>




Example Binary Kernel

Navigation and Ancillary Information Facility

A binary kernel contains lots of non-printing data, usually interspersed with occasional occurrences of ASCII characters.


Includes a “comment area” where descriptive meta-data should be placed.



Comments In SPICE Kernels

Navigation and Ancillary Information Facility

- **All SPICE kernels should contain comments—descriptive information about the data contained in the file.**
 - “Comments” are also known as “meta-data”
- **See the tutorial on comments for more information.**



Making a Text Kernel


Navigation and Ancillary Information Facility

- **Text kernels may be produced using a text editor**
 - Text kernels must contain only printing characters (ASCII values 32-126), i.e. human-readable text
 - » TAB characters are allowed but **HIGHLY DISCOURAGED**
 - » **Caution: some editors insert non-printing characters**
 - Text kernels must have each line terminated with the end-of-line indicator appropriate for the operating system you are using
 - » For Unix, PC/Linux, Mac OSX: `<LF>`
 - » For PC/Windows: `<CR><LF>`
 - » **Don't forget to insert the end-of-line indicator on the very last line of the kernel!**
 - Fortran toolkit software will detect and warn you if you try to read a non-native text kernel. (Not needed for other languages.)
 - See the **BACKUP** for information on converting text kernels between these two line termination techniques



Navigation and Ancillary Information Facility


Using Kernels



Loading Kernels - 1

Navigation and Ancillary Information Facility

- To make kernels available to a program you “load” them
- When you load a text kernel:
 - the file is opened
 - the kernel contents are read into memory
 - » variable names and associated values are stored in a data structure called the “kernel pool”
 - the file is closed
- When you load a binary kernel:
 - the file is opened
 - for SPK, CK, binary PCK and DSK files, no data are read until a read request is made by Toolkit software
 - for all practical purposes the binary file remains open unless specifically unloaded by you



Loading Kernels - 2

Navigation and Ancillary Information Facility


- **Use the FURNISH routine to load all kernels – text and binary**
 - `CALL FURNISH ('name.ext')` (Fortran)
 - `furnsh_c ("name.ext");` (C)
 - `cspice_furnsh, 'name.ext'` (IDL)
 - `cspice_furnsh ('name.ext')` (MATLAB)
 - `spiceypy.furnsh ('name.ext')` (Python using SpiceyPy)
- **Best practice: don't hard code filenames—list these in a “meta-kernel” and load the meta-kernel using FURNISH**
 - `CALL FURNISH ('meta-kernel_name')` (Fortran example)
 - Look further down for more information on meta-kernels



Navigation and Ancillary Information Facility

Meta-Kernels


These help make using SPICE easy!



What is a “Meta-Kernel”

Navigation and Ancillary Information Facility

- **A meta-kernel is a file that lists names (and locations) of a collection of SPICE kernels that are to be used together in a SPICE-based application**
 - Loading the meta-kernel causes all of the kernels listed in it to be loaded
- **Using a meta-kernel makes it easy to manage which SPICE files are loaded into your program—you don’t need to revise your code**
- **A meta-kernel is implemented using the SPICE text kernel standards**
 - Refer to the Kernel Required Reading technical reference for details
- **The terms “meta-kernel” and “FURNISH kernel” are used synonymously**



Sample Meta-Kernel


Navigation and Ancillary Information Facility

KPL/MK

```
\begindata
```

```
  KERNELS_TO_LOAD = (  
    '/home/mydir/kernels/lowest_priority.bsp',  
    '/home/mydir/kernels/next_priority.bsp',  
    '/home/mydir/kernels/highest_priority.bsp',  
    '/home/mydir/kernels/leapseconds.tls',  
    '/home/mydir/kernels/sclk.tsc',  
    '/home/mydir/kernels/c-kernel.bc',  
    '/home/mydir/kernels+',  
    '/custom/kernel_data/p_constants.tpc',  
  )
```

All the commas
are optional



Sample Meta-Kernel

Navigation and Ancillary Information Facility

KPL/MK


```
\begindata
```

```
  KERNELS_TO_LOAD = (  
    '/home/mydir/kernels/lowest_priority.bsp',  
    '/home/mydir/kernels/next_priority.bsp',  
    '/home/mydir/kernels/highest_priority.bsp',  
    '/home/mydir/kernels/leapseconds.tls',  
    '/home/mydir/kernels/sclk.tsc',  
    '/home/mydir/kernels/c-kernel.bc',  
    '/home/mydir/kernels+',  
    '/custom/kernel_data/p_constants.tpc',  
  )
```

All the commas
are optional

- The last file listed in this example (p_constants.tpc) demonstrates how to use the continuation character, '+', to work around the 80 character limitation imposed on string lengths by the text kernel standards.

- See the next two pages for some important OS-specific details!



Unix/Mac Sample Meta-Kernel

Navigation and Ancillary Information Facility

- This meta-kernel uses the `PATH_VALUES` and `PATH_SYMBOLS` keywords to specify the directory where the kernels are located.


KPL/MK

```
\begindata
```

```
  PATH_VALUES      = ( '/home/mydir/kernels' )
  PATH_SYMBOLS     = ( 'KERNELS' )
  KERNELS_TO_LOAD = (
    '$KERNELS/lowest_priority.bsp',
    '$KERNELS/next_priority.bsp',
    '$KERNELS/highest_priority.bsp',
    '$KERNELS/leapseconds.tls',
    '$KERNELS/sclk.tsc',
    '$KERNELS/c-kernel.bc',
    '$KERNELS/custom/kernel_data/p_constants.tpc'
  )
```

UNIX/MAC style path notation, using forward slashes

- Although the OS environment variable notation `$<name>` is used to refer to the symbols specified using the `PATH_VALUES` and `PATH_SYMBOLS` keywords, **these symbols are NOT operating system environment variables and are set and used for substitution by SPICE only in the context of this particular meta-kernel.**
- The '+' continuation character described on the previous page may be used to handle path strings that exceed 80 characters.



Windows Sample Meta-Kernel

Navigation and Ancillary Information Facility

- This meta-kernel uses the `PATH_VALUES` and `PATH_SYMBOLS` keywords to specify the directory where the kernels are located.


KPL/MK

```
\begindata
```

```
  PATH_VALUES      = ( 'c:\home\mydir\kernels' )
  PATH_SYMBOLS     = ( 'KERNELS' )
  KERNELS_TO_LOAD = (
    '$KERNELS\lowest_priority.bsp',
    '$KERNELS\next_priority.bsp',
    '$KERNELS\highest_priority.bsp',
    '$KERNELS\leapseconds.tls',
    '$KERNELS\sclk.tsc',
    '$KERNELS\c-kernel.bc',
    '$KERNELS\custom\kernel_data\p_constants.tpc'
  )
```

Windows style path notation, using backwards slashes


- Although the OS environment variable notation `$<name>` is used to refer to the symbols specified using the `PATH_VALUES` and `PATH_SYMBOLS` keywords, **these symbols are NOT operating system environment variables and are set and used for substitution by SPICE only in the context of this particular meta-kernel.**
- The '+' continuation character described previously may be used to handle path strings that exceed 80 characters.



Kernel Precedence Rule

Navigation and Ancillary Information Facility

- **The order in which SPICE kernels are loaded at run-time determines their priority when requests for data are made**
 - For binary kernels, data from a higher priority file will be used in the case when two or more files contain data overlapping in time for a given object.
 - » For SPKs, CKs, and binary PCKs the file loaded **last** takes precedence (has higher priority).
 - » For DSKs, use of priority will be specified via API calls
 - » Not yet supported as of N66 Toolkits
 - » Priority doesn't apply to ESQ files – all data from all loaded files are available.
 - If two (or more) text kernels assign value(s) to a single keyword using the “=” operator, the data value(s) associated with the last loaded occurrence of the keyword are used—all earlier values are replaced with the last loaded value(s).
 - Orientation data from a binary PCK always supersedes orientation data (for the same object) obtained from a text PCK, no matter the order in which the kernels are loaded.



Unloading Kernels

Navigation and Ancillary Information Facility

- The unloading of a kernel is infrequently needed for FORTRAN or CSPICE applications but is **essential** for Icy, Mice, Python and similar interpreter scripts.
 - Because of the way IDL and MATLAB interact with external shared object libraries, any kernels loaded during an IDL or MATLAB session will stay loaded until the end of the session unless they are specifically unloaded.
- The routines KCLEAR and UNLOAD may be used to unload kernels containing data you wish to be no longer available to your program.
 - KCLEAR unloads all kernels and clears the kernel pool
 - UNLOAD unloads specified kernels
 - KCLEAR and UNLOAD are only capable of unloading kernels that have been loaded with the routine FURNSH. They will not unload any files that have been loaded with older load routines such as SPKLEF (those used prior to availability of FURNSH).
- **Caution:** unloading text kernels with UNLOAD will also remove any kernel pool data provided through the kernel pool run-time data insertion/update APIs (PCPOOL, PDPOOL, PIPOOL).